

Dunlop

Таблица с налягания за камионни гуми

КАМИОНИ, ВЛЕКАЧИ И АВТОБУСИ

Джан-Размер	Товарен Индекс		Натоварване на ос		Макс. Налягане (bar)	Единична Сдвоена	Товарен Индекс	Натоварване на ос според налягането (bar)													
	Единична	Сдвоена	Единична	Сдвоена				5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0					
17.5"	7R17.5	108	107	2000	3900	5	S	108	2000												
						D	107	3900													
	8R17.5	117	116	2570	5000	6	S	117	2570												
						D	116	5000													
	8.5R17.5	121	120	2900	5600	6.25	S	121	2430	2620	2810										
						D	120	4690	5060	5420											
	9.5R17.5	129	127	3700	7000	7.5	S	129	2680	2890	3100	3300	3510	3700							
						D	127	5070	5470	5860	6250	6630	7000								
	10R17.5	134	132	4240	8000	8	S	134	2920	3150	3370	3600	3820	4030	4240						
						D	132	5500	5930	6360	6780	7190	7600	8000							
205/75R17.5	124	122	3200	6000	7.5	S	124	2320	2500	2680	2860	3030	3200								
					D	122	4340	4690	5020	5360	5680	6000									
215/75R17.5	126	124	3400	6400	7	S	126	2600	2810	3010	3210	3400									
					D	124	4890	5290	5660	6040	6400										
225/75R17.5	129	127	3700	7000	7.25	S	129	2750	2970	3190	3400	3600									
					D	127	5210	5620	6020	6420	6810										
235/75R17.5	132	130	4000	7600	7.75	S	132	2820	3050	3260	3480	3690	3900								
					D	130	5360	5780	6200	6610	7010	7410									
245/70R17.5	136	134	4480	8480	8.5	S	136	2940	3170	3400	3620	3840	4060	4270	4480						
					D	134	5550	5990	6420	6850	7270	7680	8080	8480							
265/70R17.5	139	136	4860	8960	8	S	139	3340	3610	3870	4120	4370	4620	4860							
					D	136	6160	6640	7120	7590	8060	8510	8960								
19.5"	245/70R19.5	136	134	4480	8480	8.25	S	136	3010	3240	3480	3710	3930	4160	4380						
					D	134	5690	6140	6580	7010	7440	7860	8280								
	265/70R19.5	140	138	5000	9440	7.75	S	140	3530	3810	4080	4350	4610	4880							
					D	138	6650	7180	7700	8210	8710	9200									
	285/70R19.5	146	144	6000	11200	9	S	146	3750	4050	4340	4630	4910	5190	5470	5740	6000				
					D	144	7000	7560	8100	8640	9170	9680	10200	10700	11200						
	305/70R19.5	148	145	6300	11600	8.5	S	148	3720	4010	4300	4590	4870								
					D	145	6840	7380	7910	8440	8950										
	255/70R22.5	140	137	5000	9200	8	S	140	4130	4450	4770	5090	5400	5700	6010	6300					
					D	137	7590	8190	8780	9360	9940	10500	11060	11600							
275/70R22.5	148	145	6300	11600	9	S	148	4340	4730	5140	5540	5940	6340	6740	7140	7540					
				D	145	7250	7830	8390	8950	9490	10030	10560	11090	11600							
275/80R22.5	149	146	6500	12000	8.5	S	149	4440	4790	5140	5480	5810	6140	6470	6790	7100					
				D	148	7880	8500	9110	9720	10310	10890	11470	12040	12600							
295/60R22.5	148	145	6300	11600	8.5	S	148	4130	4450	4770	5090	5400	5700	6010	6300						
				D	145	7590	8190	8780	9360	9940	10500	11060	11600								
295/80R22.5	150	147	6700	12300	9	S	150	4190	4520	4850	5170	5480	5800	6100	6410	6700					
				D	147	7690	8300	8900	9490	10060	10640	11200	11760	12300							
315/60R22.5	149	146	6500	12000	9	S	149	4070	4390	4700	5020	5320	5620	5920	6210	6500					
				D	146	7500	8100	8680	9250	9820	10380	10930	11470	12000							
315/70R22.5	152	148	7100	12600	8.5	S	152	4650	5020	5380	5730	6080	6430	6770	7100						
				D	148	8250	8900	9540	10170	10790	11400	12010	12600								
315/80R22.5	152	148	7100	12600	8.5	S	152	4650	5020	5380	5730	6080	6430	6770	7100						
				D	148	8250	8900	9540	10170	10790	11400	12010	12600								
315/90R22.5	154	150	7500	13400	9	S	154	4690	5060	5430	5790	6140	6490	6830	7170	7500					
				D	150	8380	9040	9690	10330	10960	11590	12200	12810	13400							
355/50R22.5	154	154	7500		9	S	154	4690	5060	5430	5790	6140	6490	6830	7170	7500					
				D	150	8980	9690	10390	11080	11750	12420	13080									
375/90R22.5	164	160	10000	18000	7.5	S	164	7230	7810	8370	8920	9470	10000								
				D	160	13020	14050	15060	16060	17040	18000										
385/55R22.5	160		9000		9	S	160	5630	6070	6510	6940	7370	7780	8200	8600	9000					
				D	158	5560	6010	6440	6860	7280	7700	8100	8500	8900							
385/65R22.5	160		9000		9	S	160	5630	6070	6510	6940	7370	7780	8200	8600	9000					
				D	158	5560	6010	6440	6860	7280	7700	8100	8500								
445/75R22.5	170		12000		8	S	170	8240	8900	9540	10170	10790	11400	12010	12600						
				D	168	11200	12000	12800	13600	14400	15200	16000	16800	17600	18400	19200					
495/45R22.5	169		11600		9	S	169	7250	7830	8390	8950	9490	10030	10560	11090	11600					
				D	169	11600	12400	13200	14000	14800	15600	16400	17200	18000	18800	19600					
305/70R24.5	154	149	7500	13000	8.5	S	154	4910	5300	5680	6060	6430	6790	7150	7500						
				D	149	8510	9190	9840	10490	11130	11770	12390	13000								
22.5" AND 24.5" LOW ASPECT RATIO	10R22.5	144	142	5600	10600	8.5	S	144	3670	3960	4240	4520	4800	5070	5340	5600					
					D	142	6940	7490	8030	8560	9080	9600	10100	10600							
	11R22.5	148	145	6300	11600	8.5	S	148	4130	4450	4770	5090	5400	5700	6010	6300					
					D	145	7590	8190	8780	9360	9940	10500	11060	11600							
	12R22.5	152	148	7100	12600	8.5	S	152	4650	5020	5380	5730	6080	6430	6770	7100					
					D	148	8250	8900	9540	10170	10790	11400	12010	12600							
	13R22.5	156	150	7500	13400	8.5	S	156	5240	5650	6060	6460	6850	7240	7630	8000					
					D	150	8770	9460	10150	10820	11480	12130	12770	13400							
	14R22.5	154	150	7500	13400	8.5	S	154	4910	5300	5680	6060	6430	6790	7150	7500					
					D	150	8770	9460	10150												